

10		9		8		7		6		5		4		3		2		1					
PART NUMBER		ENGINEERING NUMBER		FINISH LENGTH		PART NUMBER LEGEND																	
1300660035		1R3000A28M005G		1.64' [0.5M]		1R3000A28M005G																	
1300660036		1R3000A28M010G		3.28' [1M]		FINISHED LENGTH: M005= 0.5 METER M010= 1 METER M100= 10 METER																	
1300660037		1R3000A28M015G		4.92' [1.5M]		CABLE LENGTH TOLERANCES >.3M [1FT]: +19mm-0 [+.75in-0] .3 - .9M [1 - 3FT]: +44.5mm-0 [+1.75in-0] .9 - 1.8M [3 - 6FT]: +55.6mm-0 [+2.19in-0] 1.8 - 3.7M [6 - 12FT]: +88.9mm-0 [+3.50in-0] 3.7 - 7.3M [12 - 24FT]: +165.1mm-0 [+6.50in-0] 7.3-14.6M [24 - 48FT]: +317.5mm-0 [+12.50in-0] 14.6 - 30.5M [48-100FT]: +622.3mm-0 [+24.50in-0] OVER 30M [100FT] +2% OF FINISHED LENGTH																	
NOTES: 1. MATERIAL: AS NOTED 2. FINISH: AS NOTED 3. ELECTRICAL: VOLTAGE: 500V PER IEC60664 600V PER UL2237 CURRENT: 15A 4. TEMP RATING: -20°TO +90°C 5. PROTECTION: IP67 (WHEN MATED) 6. COUPLING THREAD: 7/8-16UN 7. UL LISTED FILE: E258922 8. ALL DIMS ARE FOR REFERENCE UNLESS NOTED OTHERWISE																							
6		5		4		3		2		1		6		5		4		3		2		1	
FLAG LABEL		VINYL		BLACK/YELLOW		POTTING MATERIAL		EPOXY		BLACK		WIRE, 14 AWG, UL 1015 (B)		PVC INSULATION		SEE FACE VIEW		CONTACT SOCKET		COPPER ALLOY		GOLD PLATED	
FEMALE INSERT		PVC		BLACK		RECEPTACLE SHELL		ZINC DIE-CAST		NICKEL PLATE		ITEM		DESCRIPTION		MATERIAL		FINISH					
6		5		4		3		2		1		6		5		4		3		2		1	