

N=Number of poles

Dim.A	(N-1)x10.0
Dim.B	Nx10.0+2.0

A&B Tolerance Δ

Poles	Dim.A	Dim.B
2p-9p	± 0.30	± 0.30
10p-20p	± 0.40	± 0.40
21p-32p	± 0.50	± 0.50

SIGN	DATE	DESCRIPTION	APPROVER
Δ	5/20'09	Add approval "CULUS"	Eris
Δ	10/08'09	Tolerance is changed	Eris
Δ	11/13'12	Change the screw plating specification	Guoxue
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

MATERIALS ELECTRICAL

RATED VOLTAGE & CURRENT:

300 V, 20 A

WITHSTAND VOLTAGE:

AC 2000 V/Min

INSULATION RESISTANCE:

1000 M Ω OR MORE AT DC 500 V

OPERATING TEMPERATURE RANG:

-40 °C ~ +115 °C

SCREW TORQUE VALUE:

12Lb-In.

WIRE RANGE:

22 - 12 AWG

1) MOLDED PARTS:

THERMOPLASTIC, UL 94 V-0 BLACK



2) TERMINAL:

BRASS, 0.8t, Tin PLATED

3) TERMINAL SCREWS:

STEEL, M3.5

Δ APPROVAL: 
Critical dimension: ∇




YK 61A xx 0 x x 00G

NO. OF POLES
02: 2 POLES
03: 3 POLES
04: 4 POLES
:
32: 32 POLES

G RoHS compliant
(lead<4%)
In copper Alloy


MARK
0: "@" MARK
1: "ANY" MARK
3: NO MARK
TERMINAL & SCREW PLATED
0: TERMINAL & SCREW: G/F
 Δ 1: TERMINAL: G/F, SCREW: ZINC
2: TERMINAL: Sn, SCREW: G/F
 Δ 3: TERMINAL: Sn, SCREW: ZINC



ANYTEK

INSPECTION COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		YK-61A W/O Flange Series			
PART NO.	YK61Axx0xx00G			DWG NO.	8YK0001-61A
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Guoxue 2012.12.01	Guoxue 2012.12.01		Tolerance X. ± 0.50 X.X ± 0.30 X.XX ± 0.10 X° $\pm 1^\circ$
SHEET: 01/01		UNIT: mm SCALE: NONE		REV.: D	