


LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
HG	-		A	ECO-07-016319	16JUL2007	DHR	DHR
			B	REV PER ECR-10-010066	20MAY2010	IL	CT



1 MATERIAL: PROTECTIVE COVER: TPE, COLOR: BLACK, UL 94 HB. *
FERRULE SUB ASSEMBLY: ZIRCONIA/ALUM. ALLOY
COMPRESSION SPRING: STAINLESS STEEL.
FRONT HOUSING: PPSU, COLOR BLUE, UL 94 V-0. *
REAR BODY: ALUM. ALLOY
DUPLEX CLIP: PEI, COLOR: BLACK, UL 94 V-0. *
BOOT: PP, COLOR: BLUE, UL 94 V-0. *
CRIMP EYELET/HEAT SHRINK ASSY: ALUM. ALLOY, HEAT SHRINK: POLYOLEFIN, UL VW-1.
* RATED AT QUALIFYING THICKNESS.

2 BULK PACKAGE

3. THIS IS A NON-PULL PROOF LC CONNECTOR.
IT IS DESIGNED FOR USE WITH TIGHT CONSTRUCTION OPTICAL CABLE.
UNDER LOADS YOU MAY SEE ENDFACE ABRASIONS.





CONNECTOR SUB-ASSEMBLY



DUST COVER

CRIMP EYELET/
HEAT SHRINK ASSEMBLY

DUPLEX CLIP



2	6828130-2
	6828130-1
	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT FOR TYCO ELECTRONICS CORPORATION IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.		DWN E. HALEY 14OCT2005	Tyco Electronics Corporation Shanghai, China			
DIMENSIONS: mm [INCHES]		CHK D. ROHDE 14OCT2005				
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D. ROHDE 14OCT2005	NAME CONNECTOR KIT, LC, DUPLEX, SM, JUMPER, TIGHT JACKET STYLE, 1.6 - 2.0mm			
0 PLC ± 1 PLC ±0.1 [.004] 2 PLC ±0.01 [.0004] 3 PLC ± 4 PLC ± ANGLES ± FINISH ±		PRODUCT SPEC - APPLICATION SPEC - WEIGHT -				
MATERIAL 1		CUSTOMER DRAWING	SIZE A2	CAGE CODE -	DRAWING NO 6828130	RESTRICTED TO -
			SCALE 2:1	SHEET 1	OF 1	REV B