


LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
GP	00						
			M	REVISED PER ECO-14-011808	09AUG2014	AP	SB


D




C

B


A



- CONNECTOR ACCEPTS SIZE 20 DF SOCKET CONTACTS, RETENTION TINES ARE AN INTEGRAL PART OF INSERT.
- CONNECTOR COMPLIES WITH 108-40005 WHERE APPLICABLE.
- MOLDED PARTS: GLASS-FILLED PBT OR GLASS-FILLED NYLON, UL94V-0 RATED. COLOR: BLACK
- SHELLS: STEEL PER ASTM A109.
- ZINC PLATED PER ASTM B633; TYPE II; CLASS SC1; YELLOW CHROMATE.
- TIN PLATED PER MIL-T-10727 OVER COPPER PER MIL-C-14550.
- CHROME PLATED.
- ZINC PLATED .000200-.000400 THICK, YELLOW TRIVALENT CHROMIUM CHROMATE COATING.



OBSOLETE	STANDARD	8	205203-8
	SMALL PACK	5	205203-6
OBSOLETE	STANDARD	6	205203-3
	STANDARD	5	205203-1
PACKAGING TYPE		SHELL FINISH	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. WELDON	7-19-85	 TE Connectivity							
		CHK J. GERACE	7-29-85								
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD V. KUMAR	7-31-85	NAME RCPT CONNECTOR, SIZE 1, 9 POSN, AMPLIMITE , HDP —							
	0 PLC ± —	PRODUCT SPEC	—								
	1 PLC ± —	APPLICATION SPEC	—								
	2 PLC ± 0.13 [.005]										
	3 PLC ± —										
4 PLC ± —	—	SIZE	CAGE CODE	DRAWING NO		RESTRICTED TO					
MATERIAL	FINISH	WEIGHT	—	A2	00779	C-205203		—			
SHELLS: SEE TABLE		CUSTOMER DRAWING				SCALE	4:1	SHEET	1 of 1	REV	M