



TECHNICAL:
LISTED:
 RATED SUPPLY VOLTAGE: 120 VAC
 RATED CURRENT: UP TO 15 AMPS OR CABLE RATING
 RESET TYPE: AUTOMATIC OR MANUAL
 OPERATING FREQUENCY: 60 Hz
 TYPE: CLASS A
 GROUND TRIP CURRENT: 4-6 mA
 OVERLOAD CURRENT: 90 AMP 125 VAC
 INSULATION VOLTAGE: 1,500 VRMS – 1 MINUTE
 ENDURANCE OPERATIONS: 3000 OPERATIONS

UL AND cUL
 120 VAC
 UP TO 15 AMPS OR CABLE RATING
 AUTOMATIC OR MANUAL
 60 Hz
 CLASS A
 4-6 mA
 90 AMP 125 VAC
 1,500 VRMS – 1 MINUTE
 3000 OPERATIONS

MATERIAL NO.	ENGINEERING NO.	LENGTH "L"	POWER-UP
1301530093	15054-1TTA	2 FT ± 1 IN	AUTO
1301530097	15054-25TTA	25 FT ± 2 IN	AUTO
1301530094	15054-1TTA	2 FT ± 1 IN	MANUAL
1301530098	15054-25TTM	25 FT ± 2 IN	MANUAL

INITIAL RELEASE EC NO: IPG2013-1078 DRWN: HRUIZ01 2013/02/07 CH'KD: HKNEELAN 2014/07/22 APPR: JFMURPHY 2015/04/20	DESCRIPTION REV	QUALITY SYMBOL ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION				
					INCH		NTS	INCH					
					mm	INCH	DRAWN BY	DATE	TITLE				
					4 PLACES	±---	±---	HRUIZ01	2013/02/07	120V 15A PLUG GFCI W/ MOLDED TRIPLE TAP NEMA 5-15			
		3 PLACES	±---	±.005	CHECKED BY	DATE	MOLEX INCORPORATED						
		2 PLACES	±0.13	±.010	HKNEELAN	2014/07/22	DOCUMENT NO. SD-130153-018						
		1 PLACE	±0.25	±.020	APPROVED BY	DATE	SHEET NO. 1 OF 1						
		ANGULAR ±1/2°			JFMURPHY	2015/04/20	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			MATERIAL NO. SEE TABLE								
					SIZE C								