

Cable gland - G-INS-NPT3/8-S68L-NNES-S - 1411182

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 5 mm ... 10 mm, Shielding: No, Connecting thread: NPT3/8 inch, Color: silver

Product Features



Key commercial data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	24.0 GRM
Custom tariff number	74199990
Country of origin	Turkey

Technical data

Dimensions

Length	34.5 mm
Length without connecting thread	23 mm
Connecting thread diameter	16 mm
Wrench size, union nut	17 mm
Wrench size, support	19 mm
Hexagon angular dimension GRP	22 mm
Length of the connecting thread	11.5 mm
External cable diameter	5 mm ... 10 mm

Ambient conditions

Degree of protection	IP68
Ambient temperature (operation)	-40 °C ... 100 °C

General

Cable gland - G-INS-NPT3/8-S68L-NNES-S - 1411182

Technical data

General

Cable gland material	Brass, nickel-plated
Seal material	CR
Cable seal material	CR
O-ring material	NBR
Shielded	No
Thread type on connection side	NPT3/8 inch
Torque	8 Nm ... 10 Nm (Union nut)
Color	silver

Classifications

eCl@ss

eCl@ss 5.1	27081002
eCl@ss 6.0	27081002
eCl@ss 8.0	27149109

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Approvals

Approvals


Approvals

UL Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized 

Cable gland - G-INS-NPT3/8-S68L-NNES-S - 1411182

Drawings

Dimensional drawing

