




D-SUBMINIATURE CONNECTORS:

K42X Series

High Density Dual-Port D-Sub

K42X Series Dimensions

Dimensions in mm



Number of Contacts (Shell Size)	Dimensions (Inch/ mm)			
	A	A1	B	C
9 (E)	.643 16.33	.666 16.92	.984 24.99	1.213 30.81
15 (A)	.971 24.66	.994 25.25	1.312 33.32	1.541 39.14
25 (B)	1.511 38.38	1.534 38.96	1.852 47.04	2.088 53.04
37 (C)	2.159 54.84	2.181 55.42	2.500 63.50	2.729 69.32

Center to Center Spacing	D	E
A	.750 19.05	1.244 31.60
B	.900 22.86	1.394 35.41
C	.625 15.88	1.119 28.42

A = Exterior of Female Shell (S)

A1 = Interior of Male Shell (P)

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number

K42X-A26S/S-A4N

Part Number Builder

K42X	-	A26 S	A26 S	A	4N	
Series		Top/Bottom Shell Size	Bottom Shell Size	Center Distance	Boardlock Option	Jackscrews Option

Series

K42X - High Density Dual-Port D-Subminiature Connector

Top/Bottom Shell Size

A26S/S - 26 Contacts, Receptacle over Receptacle

B44S/S - 44 Contacts, Receptacle over Receptacle

E15S/P - 15 Contacts, Receptacle over Plug

E15S/S - 15 Contacts, Receptacle over Receptacle

Center to Center Distance

A - 0.750" (Standard)

Boardlocks Option

4N - Boardlocks (Standard)

Jackscrews Option

Blank - No Jackscrews

J - 4-40 Jackscrews Installed

Contact Kycon for Other Options