

6

5



4

3



2

1

MATERIAL NUMBER	ENGINEERING NO.	LENGTH ± TOLERANCE
1300500457	ENP3335M010	3' 3" +2.19"/-0" [1M +55.6/-0 mm]
1300500193	ENP3335M050	16' 4" +6.50"/-0" [5M +165.1/-0 mm]

AUX VIEW
SCALE 1:4

MALE - FACE VIEW



MALE - FACE VIEW

P1		P2
1	WHITE/ORG	1
2	ORANGE	2
3	WHITE/GRN	3
4	BLUE	4
5	WHITE/BLUE	5
6	GREEN	6
7	WHITE/BROWN	7
8	BROWN	8
SHLD	SHIELD	SHLD

WIRING DIAGRAM

NOTES:

- 1) MATERIAL: SEE TABLE
- 2) FINISHES: SEE TABLE
- 3) CABLE: #26/8 SHIELDED TWISTED PAIR, PUR
- 4) ELECTRICAL DATA:
ACCORDING TO CAT5e ETHERNET STANDARD
MAX. VOLTAGE: 30V
MAX. CURRENT 1.5A
- 5) ENVIRONMENTAL:
PROTECTION IP67
TEMPERATURE RANGE: -20°C TO +80°C
- 6) WRAP LABEL IS MARKED WITH P/N & DATE CODE.
- 7) ASSEMBLY IS RoHS COMPLIANT.

4	1	LABEL	PLASTIC FILM	BLACK/YELLOW
3	2	RJ45 PLUG	POLYCARBONATE	CLEAR
2	2	BOOT	PVC	BLACK
1	1	ETHERNET CABLE-CAT5E	PUR JACKET	BLACK
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

SD RELEASE EC NO: WNA2010-0016 7/23/09 DRWN: VOU CHKD: BWOODMAN APPR: JFMURPHY 2009/08/10		QUALITY SYMBOLS ▽=0 ▽C=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 3:4	DESIGN UNITS INCH	THIRD ANGLE PROJECTION		
				mm	INCH	DRAWN BY VOU		DATE 2009/07/15	TITLE ETHERNET CABLE ASSY 8P M/M STD/STD 568B #26/8 SHIELDED CABLE		
			4 PLACES	±----	±----	CHECKED BY BWOODMAN		DATE 2009/07/31			
			3 PLACES	±----	±.005	APPROVED BY		DATE	MOLEX INCORPORATED		
2 PLACES	±----	±.010	MATERIAL NO.		DOCUMENT NO.	SHEET NO.					
1 PLACE	±----	±.020	SEE CHART		SD-130050-004		1 OF 1				
		ANGULAR ±1/2°		SIZE A		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS									

6

5

4

3

2

1