

# GPS Active Antenna Module- Magnet Mount

**APAMP-124**



**ESD Sensitive**

**RoHS/RoHS II compliant**

**Lead in copper alloy exemption (6c); and Lead in glass exemption (7c-I)**



49.20 X 40 X 15.20mm

**MSL level: Not Applicable**

## FEATURES:

- High Reliability/Sensitivity
- Compact Size
- Easy to install (magnet base)
- ROHS Compliant

## TYPICAL APPLICATIONS:

- Automotive Navigation
- Automotive Monitoring
- Personal Tracking

## STANDARD SPECIFICATIONS:


### Antenna

| Parameters               | Min.    | Typ.    | Max.    | Units    | Note                               |
|--------------------------|---------|---------|---------|----------|------------------------------------|
| Frequency                | 1574.40 | 1575.42 | 1576.44 | MHz      |                                    |
| Bandwidth                | 10.0    |         |         | MHz      |                                    |
| VSWR at Center Frequency |         |         | 1.5:1   |          |                                    |
| Polarization Model       | RHCP    |         |         |          | (Right Hand Circular Polarization) |
| Impedance                |         | 50      |         | $\Omega$ |                                    |
| Gain                     |         | 5       |         | dBic     | (Based on 70× 70mm ground plane)   |
| Operating Temperature    | -40     |         | +80     | °C       |                                    |
| Storage Temperature      | -45     |         | +85     | °C       |                                    |

### Low Noise Amplifier (LNA)

| Parameters   | Min.    | Typ.    | Max.    | Units | Note           |
|--------------|---------|---------|---------|-------|----------------|
| Frequency    | 1574.40 | 1575.42 | 1576.44 | MHz   |                |
| DC Voltage   | 2.5     | 3.0     | 3.5     | V     |                |
| Gain         | 27      | 29      | 31      | dB    | (+25°C ± 10°C) |
| Output VSWR  |         |         | 2.0     |       |                |
| Noise Figure |         |         | 2.0     |       | (+25°C ± 10°C) |
| DC current   |         | 9.5     | 12      | mA    | (At 3.0V)      |

## ANTENNA'S IMPEDANCE AND RETURN-LOSS CHARACTERISTICS



S11: Input VSWR

Test condition: 27x27mm ground

# GPS Active Antenna Module- Magnet Mount

APAMP-124




ESD Sensitive

RoHS/RoHS II compliant  
Lead in copper alloy exemption (6c); and Lead in glass exemption (7c-I)




49.20 X 40 X 15.20mm

## LNA REFLECTION PROFILE



S21: LNA Gain

## OUTLINE DRAWING:



Top View

Side View

Bottom View

Unit:mm

| Parameters       | Description        |
|------------------|--------------------|
| L (Cable Length) | 300±10cm           |
| Antenna          | Dielectric Ceramic |
| RF Cable         | RG174              |
| PCB              | FR4                |
| RF Connector     | SMA-JW3            |
| Shielding        | Tinplate           |
| Thickness        | 15.5mm             |
| Mounting Type    | Magnet Base        |

# GPS Active Antenna Module- Magnet Mount

**APAMP-124**



**ESD Sensitive**

**RoHS/RoHS II compliant**

**Lead in copper alloy exemption (6c); and Lead in glass exemption (7c-I)**



49.20 X 40 X 15.20mm

## PRODUCT IMAGE:



## PACKAGING:

Each 475 x 215 x 215 mm size carton includes 100 pieces of antenna.



### CAUTION:

- (1) Do not apply excess mechanical stress to the component body or terminations. Do not attempt to re-form or bend the components as this will cause damage to the component.
- (2) Do not expose the component to open flame.
- (3) This specification applies to the functionality of the component as a single unit. Please insure the component is thoroughly evaluated in the application circuit.

**ATTENTION:** Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS  
ISO9001:2008  
CERTIFIED



**ABRACON  
CORPORATION**

Visit [www.abracon.com](http://www.abracon.com) for Terms & Conditions of Sale **Revised: 10.28.14**  
30332 Esperanza, Rancho Santa Margarita, California 92688  
tel 949-546-8000 | fax 949-546-8001 | [www.abracon.com](http://www.abracon.com)