

M23 HMB angled – rotatable



| | |
|--------------------|---|
| Part number | 09 15 100 0902 |
| Specification | M23 HMB angled – rotatable |
| HARTING eCatalogue | https://b2b.harting.com/09151000902 |

Identification

| | |
|-----------------------------|--------------------------|
| Category | Hoods/Housings |
| Series | Circular connectors M23 |
| Identification | Signal |
| Type of hood/housing | Bulkhead mounted housing |
| Description of hood/housing | Front mounting |
| | Angled |
| | Rotatable |

Version

| | |
|--------------|------------------------|
| Locking type | Screw locking |
| | ComLock rapid locking |
| Size | M23 |
| Fixing | Fixing hole 4 x 2.7 mm |

Technical characteristics

| | |
|--|---|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP67 in locked position |
| | IP69 / IPX9K acc. to ISO 20653 in locked position |

Material properties

| | |
|-------------------------|-------------------|
| Material (hood/housing) | Copper-zinc alloy |
| Surface (hood/housing) | Nickel plated |
| Material (seal) | NBR |
| Colour (seal) | Black |
| RoHS | compliant |



Pushing Performance

Material properties

| | |
|-----------------------------|-----------|
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| | |
|----------|-----------------------|
| UL / CSA | UL 1977 ECBT2.E235076 |
|----------|-----------------------|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 5 |
| Net weight | 86 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440224 Shell for circular connectors |