


B



1. DIMENSIONS IN BRACKETS () ARE METRIC [mm].
2. PRODUCT DESIGNED AS OPTIONAL METHOD TO CONNECT ADJOINING QB-TILES.
3. PRODUCT IS RATED FOR ENVIRONMENTAL CONDITIONS OF 40-100°F IN ALL HUMIDITY RANGES.
4. PRODUCT IS 20% GF NYLON WITH ALUMINUM INSERTS
5. COMPATIBLE WITH FLATHEAD PHILLIPS DRIVE #10-32 X 1-1/4" SCREWS (INCLUDED).

A

TITLE		QUICK-BUILD GRID CONNECTOR; OPTIONAL TO SECURE TILES; 5 PER PACKAGE (QB-CONN)			
		CUSTOMER DRAWING			
ITEM REVISION NAME		14L203AU/01			
DATASET FILE NAME		14L203AU-DC			
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm] .x ± .1 [2.54] .xxx ± .005 [.127] .xx ± .01 [.25] ANGLES ± 5 °  THIRD ANGLE PROJECTION				MATERIAL : SEE NOTES	
				DRAWING NUMBER: 14L203AU-DC	
DRAWN BY	DATE	CHK	SCALE	SIZE	
ANF	07-01-15	DJW	1:1	SHT 1 OF 1	
				A	