Product datasheet **Characteristics**

XCSTE5543

Green Premium



Main		
Device short name	XCSTE	
Enclosure type	Enclosure corrosion resistance indoor/outdoor Enclosure dust and damp proof indoor/outdoor	

Complementary

Line Dated Current		
Line Rated Current	6 A	
[Us] rated supply voltage	230 V	
Actuator	Кеу	
Contact operation	Slow-break, break before make	
Depth	1.3 in	
Electromagnet interlocking	Locking on energisation and unlocking on de-energisation of solenoid	
Enclosure material	Plastic	
Height	3.67 in	
Locking options description	With interlocking, locking by solenoid With locking of actuator, unlocking by key operated lock	
Number of poles	2	
Permissible voltage	<= 300 V AC	

Environment

ambient air temperature for operation	-13140 °F
IP degree of protection	IP67
NEMA degree of protection	NEMA 4/4X/12

Offer Sustainability

Green Premium product	Green Premium product	
Compliant - since 1150 - Schneider Electric declaration of conformity	Compliant - since 1150 - Schneider Electric declaration of conformity	
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold	
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:	
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm. harm.		
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov	

Contractual warranty

Warranty period

18 months

