




REV.	DATE	ECR NO.	DESCRIPTION
NC	02/02/09	–	INITIAL RELEASE



RECOMMENDED CABLE STRIPPING DIM'S

NOTE:

1. CRIMPED FERRULE HEX CRIMP SIZE .213" [5.41]
2. CRIMPED CONTACT PIN HEX CRIMP SIZE .068" [1.72]

				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007” .315 – 1.180 = ± 0.015” 1.180 – 4.724 = ± 0.020” DO NOT SCALE DRAWING	APPROVALS		DATE		Amphenol Connex							
8					DRAWN	GRS	02/02/09									
7					CHECKED											
6									PART DESCRIPTION BNC R/A CRIMP PLUG (FOR RG-223/U, 400/U, 55/U, 142A/U)							
5																
4	FERRULE	COPPER	NICKEL		1											
3	CONTACT PIN	BRASS	GOLD		1					PART NO. 112725						
2	INSULATOR	PTFE	NATURAL		1											
1	BODY	BRASS	NICKEL	1												
				CAD FILE		C:/112/112725.DWG		DWG. NO.		112725.DWG	REV.	NC	SIZE	A	SCALE	NA