



Features:

- ✓ The modified “ T “ adapter maximizes space by allowing BNC cables to connect straight into the body instead of the side as with conventional “ T “ adapters.
- ✓ Ideal for cross-connect panels requiring multiple BNC connections.
- ✓ Adapter is precision machined (not die-cast) from brass.

Materials:

| | |
|-----------------------|-----------------------------|
| Connector Body | Nickel plated brass |
| Center Contact Pin | Gold plated brass |
| Center Contact Socket | Gold plated phosphor bronze |
| Insulator | Polybutylene Terephthalate |
| Rubber Gasket | Silicone rubber |

Ratings:

| | |
|------------------------|--------------------|
| Impedance: | 50 Ohms |
| Frequency: | 0 to 4 GHz |
| VSWR: | 1.30 max |
| Contact Resistance: | 3 Milliohms max. |
| Voltage | * 500 V |
| Insulation Resistance: | 5,000 Megohms min. |
| Insertions: | 500 |
| Temperature: | -40 to +85 C |

* *Hands free testing* in controlled voltage environment: *For CE compliance:* not intended for hand held use at voltages above 33 Vrms / 70 Vdc.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02” (.51 mm), .xxx = ± .005” (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Sales: 800-490-2361 Fax: 888-403-3360 Technical Assistance: 800-241-2060
For “Where to Buy” information, visit the Pomona web site at www.pomonaelectronics.com