

ZFKDSA 2,5-5,08-3 EX 2RZ - 1705934

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



PCB terminal block, pitch: 5.08 mm, number of positions: 3, connection method: Spring-cage connection, mounting: Wave soldering, color: green

The figure shows a 1-pos. version of the product

Your advantages

- ☑ Defined contact force ensures that contact remains stable over the long term
- ☑ Clamping space opened by means of fixed screwdriver enables convenient conductor connection
- ✓ Angled connection enables multi-row arrangement on the PCB
- Satisfies the more stringent safety requirements of "Ex e" protection according to IEC 60079-7 for potentially explosive areas
- The latching on the side enables various numbers of positions to be combined



Key Commercial Data

Packing unit	50 pc			
GTIN	4 046356 808736			
GTIN	4046356808736			

Technical data

Dimensions

Pitch	5.08 mm
Dimension a	10.16 mm
Height	15 mm
Solder pin [P]	3.5 mm
Hole diameter	1.3 mm

General

Range of articles	ZFKDS(A) 2,5-EX
Nominal cross section	2.5 mm ²
Number of positions	3



ZFKDSA 2,5-5,08-3 EX 2RZ - 1705934

Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals				
Approvals				
Approvals				
EAC				
Ex Approvals				
EAC Ex				
Approval details				
EAC	EAC			B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com