Product datasheet Characteristics

XCKD2149N12

Body type	Compact
Device short name	XCKD
Range of product	OsiSense
Series name	General duty

Complementary

Line Rated Current	10 A
Associated body	ZCD21
Associated head	ZCE01
Body material	Metal
Contact operation	Snap action
Height	55100.5 mm
Positive opening	With
Product weight	0.54 lb(US)
Size	50 x 10 mm roller
Switch actuation	CW and CCW
Torque value	14.16 ozf.in

Environment

		· · · · · · · · · · · · · · · · · · ·
ambient air temperature for operation	-13158 °F	-
environmental characteristic	RoHS compliant	
IP degree of protection	IP66 IP67	
NEMA degree of protection	NEMA 1/2/4/6/12/13	
product certifications	CE CSA UL listed	
shock resistance	50 gn	
standards	CENELEC EN 50047	
vibration resistance	25 gn	_

Offer Sustainability

WARNING: This product can expose you to chemicals including:		WARNING: This product can expose you to chemicals including:	
	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	

Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm.

F	For more information go to www.p65warnings.ca.gov
For more information do to www phowarnings ca dov	For more information do to www phowarnings ca dov

Contractual warranty

Warranty period 18 months	
---------------------------	--