

Caps to Holder FEC



500 VAC · 4 W / 10 A (VDE) · 600 VAC/DC · 20 A (UL/CSA)

**Standards**

- IEC 60127-6
- UL 4248-1
- CSA 22.2 no. 4248-1

Approvals


- VDE Certificate Number: 137910 UG
- UL File Number: E39328

ReferencesFits to type: [FEC](#)**Weblinks**

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [Approvals](#), [RoHS](#), [CHINA-RoHS](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

Technical Data

Fuse-Link	5 x 20 or 6.3 x 32 mm
Rated Voltage	500 VAC (VDE), 600 VAC/DC (UL/CSA)
Rated Current	10 A (VDE), 20 A (UL/CSA)
Rated Power Acceptance IEC	4 W / 10 A @ Ta 23 °C
Degree of Protection	IP 40
Admissible Ambient Air Temp.	-40 °C to 85 °C
Material: Cap	Thermoset
Storage Conditions	0 °C to 60 °C, max. 70% r.h.

Dimensions**Variants**

Cap	Fuse-Link	Degree of Protection	Order Number
Slot Knob	5 x 20 mm	IP 40	0031.1611
Slot Knob	6.3 x 32 mm	IP 40	0031.1613
Fingergrip	6.3 x 32 mm	IP 40	0031.1616

Packaging Unit

Plastic Bag (100 pcs.)