

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [120615-1006](#)  
**Status:** **Active**  
**Overview:** Brad® Ultra-Lock® (M12) EX Connection System for Zone 2 Hazardous Locations  
**Description:** Ultra-Lock® (M12) EX Receptacle, 5 Poles, 1/4" - 18 NPT, Male (Straight) to 22 AWG PVC Cable, 0.30m (11.81") Length

**Documents:**

[Drawing \(PDF\)](#)

[RoHS Certificate of Compliance \(PDF\)](#)

**General**

Product Family	Industrial Receptacles
Series	<a href="#">120615</a>
IP Rating	IP69K
NEMA Rating	NEMA 6
Overview	<a href="#">Brad® Ultra-Lock® (M12) EX Connection System for Zone 2 Hazardous Locations</a>
Product Name	Ultra-Lock® (M12) EX
Type	Single Ended (pigtail)
UPC	78172535801

**Physical**

Coupling Type	Internal Thread
Gender	Male
Keyway	Single
Length	0.30m
Material - Component	Nickel-plated Brass
Mounting Thread Size	1/4" - 18 NPT
Orientation	Straight
Panel Mount	Front
Poles	5
Temperature Range - Operating	-20°C to +80°C
Wire Size AWG	22
Wire/Cable Type	UL 1061

**Electrical**

Current - Maximum per Contact	4.0A
Voltage - Maximum	32V

**Material Info**

Old Part Number	LWR5A06A18C300
-----------------	----------------

**Reference - Drawing Numbers**

Sales Drawing	SD-120614-999, SD-120615-004
---------------	------------------------------



**EU RoHS**

**ELV and RoHS Compliant**  
**REACH SVHC**  
 Not Reviewed  
**Low-Halogen Status**  
 Not Reviewed

**China RoHS**



**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**

120615Series