





THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN1770155	2017/07/11	Vicky	Update Note



Pin Assignments
Front View 前視圖

- Note:
- * $\varnothing$ Important Dimension
 - * Waterproof Rate: IP66
 - * Ring: EPDM, Black
 - * Housing: Nylon+GF, Black
 - * Male Pin: Copper Alloy, Gold Plated
 - * Screw Nut: Nylon+GF, Black
 - * Seals: EPDM, Black
 - * Clamping Ring: Nylon+GF, Black
 - * Sealing Nut: Nylon+GF, Black
 - * PE Bag: 90mm*85mm
 - * Liquid Glue: Clear
 - * Seals B1 for Cable OD: $\varnothing$ 4.5mm~ $\varnothing$ 6.5mm (防水墊圈B1線徑: $\varnothing$ 4.5mm~ $\varnothing$ 6.5mm)
 - * Seals B2 for Cable OD: $\varnothing$ 3.5mm~ $\varnothing$ 5.3mm (防水墊圈B2線徑: $\varnothing$ 3.5mm~ $\varnothing$ 5.3mm)
 - * One Set Unassembled in One PE Bag (每一組未組裝, 放置於一個PE袋, 並封口)

A	UNIT:mm				TITLE		Standard,Assy Screw 6Pin F Conn M Pin		Amphenol LTW 安費諾亮泰企業股份有限公司		ITEM NO		DRAWN BY		DATE	
	TOLERANCE				SCALE						SIZE		SHEET		OF	
	.X ±0.25				1:1		A4				1		OF		2017-07-11	
	.XX ±0.1														2017-07-11	
	.XXX ±0.05														2017-07-11	
ANGLES ±1°				REV.		WC-REV.		QC: Inspection item		CUSTOMER		APPROVED BY		DATE		
				B		A.2				ALTW		Max		2017-07-11		
1		2		3		4		5		6		7		8		
														FMW10702-01-02A1		