



## Main

|                               |                                                        |
|-------------------------------|--------------------------------------------------------|
| Range of product              | OsiSense XX                                            |
| Sensor type                   | Ultrasonic sensor                                      |
| Series name                   | General purpose                                        |
| Sensor name                   | XX6                                                    |
| Sensor design                 | Cylindrical M30                                        |
| Detection system              | Diffuse                                                |
| [Sn] nominal sensing distance | 3.28 ft (1 m) adjustable with remote teach push-button |
| Material                      | Plastic                                                |
| Type of output signal         | Discrete                                               |
| Discrete output function      | 1 NO                                                   |
| Wiring technique              | 3-wire                                                 |
| Discrete output type          | NPN                                                    |
| [Us] rated supply voltage     | 12...24 V DC with reverse polarity protection          |
| Electrical connection         | Male connector M12 4 pins                              |
| [Sd] sensing range            | 0.33...3.28 ft (0.1...1 m)                             |
| Beam angle                    | 7 °                                                    |
| IP degree of protection       | IP67 conforming to IEC 60529                           |

## Complementary

|                                                   |                                                                                                     |
|---------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Enclosure material                                | Valox                                                                                               |
| Front material                                    | Epoxy                                                                                               |
| Thread type                                       | M30 x 1.5                                                                                           |
| Supply voltage limits                             | 10...28 V DC                                                                                        |
| [Sa] assured operating distance                   | 0.33...3.28 ft (0.1...1 m) (teach mode)                                                             |
| Maximum differential travel                       | 0.1 in (2.5 mm)                                                                                     |
| Blind zone                                        | 0...3.94 in (0...100 mm)                                                                            |
| Transmission frequency                            | 180 kHz                                                                                             |
| Repeat accuracy                                   | 0.9 %                                                                                               |
| Deviation angle from 90° of object to be detected | -7...7 °                                                                                            |
| Minimum size of detected object                   | Cylinder diameter 50.8 mm at 3.28 ft (1 m)                                                          |
| Status LED                                        | 1 LED (dual colour) setting-up assistance<br>1 LED (green) supply on<br>1 LED (yellow) output state |
| Current consumption                               | 60 mA                                                                                               |
| Maximum switching current                         | 100 mA with overload and short-circuit protection                                                   |
| Voltage drop                                      | < 1 V                                                                                               |
| Switching frequency                               | <= 70 Hz                                                                                            |
| Delay first up                                    | 75 ms                                                                                               |
| Delay response                                    | 15 ms                                                                                               |
| Delay recovery                                    | 75 ms                                                                                               |
| Marking                                           | CE                                                                                                  |
| Threaded length                                   | 1.46 in (37 mm)                                                                                     |
| Height                                            | 3.78 in (96 mm)                                                                                     |
| Width                                             | 1.18 in (30 mm)                                                                                     |
| Product weight                                    | 0.2 lb(US) (0.09 kg)                                                                                |

## Environment

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                                       |                                                        |
|---------------------------------------|--------------------------------------------------------|
| standards                             | IEC 60947-5-2                                          |
| product certifications                | CCSAus<br>UL                                           |
| ambient air temperature for operation | 32...158 °F (0...70 °C)                                |
| ambient air temperature for storage   | -40...176 °F (-40...80 °C)                             |
| vibration resistance                  | +/-1 mm conforming to IEC 60068-2-6 10...55 Hz         |
| shock resistance                      | 30 gn in all 3 axes 11 ms conforming to IEC 60068-2-27 |
| resistance to electrostatic discharge | 8 kV level 4 conforming to IEC 61000-4-2               |
| resistance to electromagnetic fields  | 9.14 V/yd (10 V/m) level 3 conforming to IEC 61000-4-3 |
| resistance to fast transients         | 1 kV level 3 conforming to IEC 61000-4-4               |


## Offer Sustainability

|                                                                                                                            |                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Not Green Premium product                                                                                                  | Not Green Premium product                                                                                                  |
| Compliant - since 1140 - Schneider Electric declaration of conformity                                                      | Compliant - since 1140 - Schneider Electric declaration of conformity                                                      |
| Reference contains SVHC above the threshold - go to CaP for more details                                                   | Reference contains SVHC above the threshold                                                                                |
| Available                                                                                                                  | Available                                                                                                                  |
| WARNING: This product can expose you to chemicals including:                                                               | WARNING: This product can expose you to chemicals including:                                                               |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

## Dimensions




## Minimum Mounting Distances

### Side by side



e : respect the distances indicated on the detection curves

### Face to face




e > 4 x Sn

## Wiring Diagram


### 3-Wire Type

NO outputs, NPN



- (1) (+)
- (2) Teach input (WH)
- (3) (-)
- (4) Output
- BN Brown
- WH White
- BU Blue
- BK Black

## Curves



- (1) Parallel movement
- (2) Distance
- (3) Blind zone for diffuse sensors.