


1. RECOMMENDED SPARE PARTS.
2. GREASE RAM, CAM, CAM FOLLOWER AND FEED ROD LIGHTLY.
3. LUBRICATE DAILY PER THE APPLICATOR INSTRUCTION SHEET SUPPLIED WITH THE APPLICATOR.
4. CRIMP DATA CALCULATED BY TYCO.
5. DUE TO TERMINAL DESIGN, 12AWG WIRE SIZE CAN NOT MEET TYCO CAPABILITY STUDY VALUES FOR TENSILE VALUE REFERENCED BY 114-3118.



QTY REOD PER ASSY				PARTS LIST					
TE MC APP	11-03 OCT01 DATE	DIMENSIONS: mm (INCHES) DO NOT SCALE PRINT.		MATL	-	HT TR	-	FIN	-
		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DR	105EP01	APP	105EP01		
		1 PLC DEC ± 0.5 [0.02 IN]		M.CLIFFORD			F.BACKHURST		
		2 PLC DEC $\pm$		CHK	-	REL	23-10-01		
		3 PLC DEC $\pm$			-	M.CLIFFORD			
ANGLES $\pm$				 AMP Incorporated Harrisburg, PA 17105-3608					
SURF TEXTURE: ☒		NAME		SIDE FEED HD-I APPLICATOR				MACHINE REF	
REMOVE BURRS, BREAK SHARP EDGES RO.38 MAX		SCALE		-	DWG NO	1426243		SHEET	1 of 1
CAGE CODE 00779		CUSTOMER AND ASSEMBLY DRAWING						REV	B
								RESTRICTED TO	-