

Coaxial Panel Connector
22_SHV-50-0-6/133_N

Description

Straight bulkhead receptacle jack

Interface standards
IEC 60498_MIL-STD-348A/314



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 0.3 GHz

Mechanical Data

Chassis torque 2 Nm
Number of matings 500
Weight 0.0111 kg

Environmental Data

Operating temperature -55 °C to 100 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PS (Polystyrene)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00011058
Catalogue drawing DCA-00010449
Mounting hole DOU-00008762

Ordering Information

Single package 22_SHV-50-0-6/133_NE

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

[22_SHV-50-0-6/133_NE](#)