


| JKL PART NUMBER | LENGTH A +/- 2mm | COLOR | STARTING CIRCUIT VOLTAGE VS (Vrms) | OPERATING LAMP VOLTAGE VL (Vrms) | OPERATING LAMP CURRENT IL (mA rms) | BRIGHTNESS (CANDELA/m ²) | *RATED LIFE (HRS) |
|-----------------|---------------------|--------|------------------------------------|----------------------------------|------------------------------------|--------------------------------------|-------------------|
| BF650-20B | 50mm | RGB | 390 | 170 | 5 ± 1 | 6,500 ± 650 | 20,000 |
| BF6100-20B | 100mm | | 500 | 200 | 5 ± 1 | 6,500 ± 650 | 20,000 |
| BF6120-20B | 120mm | HIGH | 590 | 235 | 5 ± 1 | 6,500 ± 650 | 20,000 |
| BF6144-20B | 144mm | OUTPUT | 600 | 240 | 5 ± 1 | 6,500 ± 650 | 20,000 |
| BF6150-20B | 150mm | WHITE | 615 | 245 | 5 ± 1 | 6,500 ± 650 | 20,000 |
| BF6165-20B | 165mm | 5400° | 640 | 255 | 5 ± 1 | 6,500 ± 650 | 20,000 |
| BF6178-20B | 178mm | KELVIN | 675 | 270 | 5 ± 1 | 6,500 ± 650 | 20,000 |
| BF6200-20B | 200mm | (REF.) | 725 | 290 | 5 ± 1 | 6,500 ± 650 | 20,000 |
| BF6225-20B | 225mm | | 825 | 330 | 5 ± 1 | 6,500 ± 650 | 20,000 |
| BF6333-20B | 333mm | | 1125 | 450 | 5 ± 1 | 6,500 ± 650 | 20,000 |

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

METRIC



THIRD ANGLE PROJECTION

DIMENSIONS ARE IN MILLIMETERS

TOLERANCE UNLESS OTHERWISE SPECIFIED

1 PL +/- 0.2
2 PL +/- 0
ANGLE +/- 0

JKL

COMPONENTS CORPORATION

TITLE

SINGLE LEAD TIPLESS MINIATURE FLUORESCENT LAMP

A CHNG LENGTH ON BF6225-20B-220 TO 225
RELEASED - CANCEL DRAW'S BF650-20B,
BF696-20B, BF6100-20B & BF6150-20B

3/19/04
2/29/00

DRAWN BY
L. WENGSTROM

APPV'D BY DATE
J.K. 3/19/04

SIZE
A

FSCM NO.
55335

DRAWING NO.

BF 6-20B

REV. NO. DESCRIPTION/ECO NUMBER APPV'D DATE

- CAD DRAWING -
MANUAL REVISIONS NOT PERMITTED

SCALE

NONE

RELEASED DATE 2/29/00

REVISION DATE 3/19/04

REV. NO. A

SHEET 1 OF 1