

# Product data sheet

## Characteristics

# 8501KA112V20

Alternating plug in relay, 11 pin, DPDT (NC),  
120 VAC/110 VDC coil



Product availability: Non-Stock - Not normally stocked in distribution facility



### Main

Product range	8501KA
Product type	Plug-in relay
Relay type	Alternating
Contact composition	NC - DPDT
[Uc] control circuit voltage	120 V AC/DC
Horsepower rating	0.33 Hp 120 V AC 0.5 hp 240 V AC
Mounting type	Socket
Pilot light	Green indicator on LED
Control type	Toggle switch

### Complementary

Maximum switching voltage	240 V AC
Number of pins	11
Shape of pins	Tubular
For use with	8501NR61 8501NR62

### Environment

Product certifications	UL recognized UL listed CSA RoHS CE
Height	1.73 in (44 mm)
Width	1.42 in (36 mm)
Depth	3.29 in (83.5 mm)

### Ordering and shipping details

Category	21145 - 8501 KF, KL
Discount Schedule	CP2
GTIN	00785901919292
Package weight(Lbs)	0.11 kg (0.25 lb(US))
Returnability	No
Country of origin	CN

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <input checked="" type="checkbox"/> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

---

China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

---

#### Contractual warranty

---

Warranty	18 months
----------	-----------

---