

Main

| | |
|---------------------------|--|
| Range of product | D10S |
| Product or component type | Disconnect Switch |
| Line Rated Current | 200 A |
| Rated power in hp | 25 hp 120 V AC 50 hp 200/240 V AC 100 hp 480 V AC 100 hp 600 V AC |
| System Voltage | 600 V AC |
| Mounting support | Door |
| NEMA size | 4 |
| Condition of use | Service entrance rated |

Complementary

Environment

Offer Sustainability

| | |
|--|--|
| WARNING: This product can expose you to chemicals including: | WARNING: This product can expose you to chemicals including: |
| Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| For more information go to www.p65warnings.ca.gov | For more information go to www.p65warnings.ca.gov |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.