# **XZCPB45P14L10**



#### Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	Application

# Complementary

Electrical connection	M12, 12 pins elbowed female connector	
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	Without	
Cable length	32.81 ft (10 m)	
Cable outer diameter	0.33 in (8.5 mm)	_
Cable composition	12 x 0.14 mm²	
Wire insulation material	PUR	
System Voltage	30 V DC	
Line Rated Current	1.5 A	
Contact resistance	5000 μOhm	- <u>:</u>
Insulating resistance	100 MOhm	
Product weight	1.92 lb(US) (0.87 kg)	

### **Environment**

		- W
IP degree of protection	IP65 IP68 IP69K	the perform
ambient air temperature for operation	-40176 °F (-4080 °C) (static) 23176 °F (-580 °C) (flexing)	eristics o
ambient air temperature for storage	-40176 °F (-4080 °C)	aract

## Offer Sustainability

Not Green Premium product	Not Green Premium product	
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:	
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm.		
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov	