

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0755771002](#)
Status: **Active**
Overview: iPass™ Connector System
Description: 0.80mm Pitch, iPass™ I/O Surface Mount Receptacle, Vertical, Internal Application, 36 Circuit, 0.38µm Gold (Au)

Documents:
[3D Model](#) [Application Specification AS-75783-001 \(PDF\)](#)
[Drawing \(PDF\)](#) [Test Summary TS-75783-001 \(PDF\)](#)
[Product Specification PS-75783-001 \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA LR19980
UL E29179

General

Product Family I/O Connectors
Series [75577](#)
Application Wire-to-Board
Component Type Receptacle
Electrical Model Yes
Overview [iPass™ Connector System](#)
Product Name iPass+™
Type N/A
UPC 822350757058

Physical


Circuits (Loaded) 26
Circuits (maximum) 26
Color - Resin Black
Durability (mating cycles max) 25
Flammability 94V-0
Gender Receptacle
Keying to Mating Part None
Lock to Mating Part No
Material - Plating Mating Gold
Material - Plating Termination Tin
Material - Resin High Temperature Thermoplastic
Net Weight 0.857/g
Orientation Vertical
PCB Retention Yes
Packaging Type Embossed Tape on Reel
Panel Mount Mounting Holes Between Circuit
Pitch - Mating Interface 0.80mm
Plating min - Mating 0.381µm
Plating min - Termination 2.540µm
Polarized to Mating Part No
Surface Mount Compatible (SMC) Yes
Temperature Range - Operating -40°C to +80°C
Termination Interface: Style Surface Mount

Electrical

Current - Maximum per Contact 0.5A
Voltage - Maximum 30V AC

Solder Process Data

Duration at Max. Process Temperature (seconds) 015
Lead-freeProcess Capability SMC&WAVE



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Contains SVHC(2014 December 17): No

Halogen-Free

Status

Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

ELV

Green Image

Not Relevant

Search Parts in this Series

[75577](#) Series

Mates With

Internal Cable Series [79575](#) , [74563](#) , [79576](#) , [74573](#) , [79536](#) , [74562](#) , [74569](#) , [74586](#)

Use With

iPass Vertical Shell Internal Cable, [76010](#)

Max. Cycles at Max. Process Temperature	001
Process Temperature max. C	260

Material Info

Reference - Drawing Numbers

Application Specification	AS-75783-001
Electrical Model Document	EE-75577-001
Product Specification	PS-75783-001
S-Parameter Model	SP-75577-001
Sales Drawing	SD-75577-002
Test Summary	TS-75783-001

This document was generated on 07/02/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION