


KN-v3-M02-3 cable

3 m pair cable with soldered (tinned) end of wires




Connector pin-out, view into the router
(rear view of cable connector)

USED COMPONENTS:

- 2x 649 006 137 22 (4.20mm Female Terminal WR-MPC4)
- 1x 649 002 113 322 (4.20mm Female Dual Row Plug WR-MPC4)
- 1x VM03V2H-H 2x0,50 BK/RD cable length of 3m
- 1x Shrinkable tube (ca. 1cm long)

PACKAGE:

The outer diameter must not exceed 95 mm.
The cable is needed to tie using 1-2 wires.
Connector is placed inside.
The cable is wrapped in a plastic bag
of a maximum size 100x130 mm



4										
3										
2										
1	Přidáno balení, odstraněna ver. 1m	P. Hanuš	1.8.2016	M. Počtýnský	1.8.2016	P. Kopecký	1.8.2016			
0	VÝCHOZÍ DOKUMENT	P. Hanuš	14.11.2014	E. Doskočil	14.11.2014	P. Kopecký	14.11.2014			
Rev.	Description of changes	Drawn	Date	Signature	Checked	Date	Signature	Approved	Date	Signature
Length unit: mm		Assembly drawing:			 Conel s.r.o., Sokolská 71 562 04 Ústí n. Orlicí III tel./fax: 465 521 020, 021 mobile-exchange: 603 872 287 E-mail: info@conel.cz http://www.conel.cz/					
Accuracy:		Old drawing:								
Tolerance:		Commission:								
Scale:	Format: A4	File: VKA-2014-03-1.dwg								
Drawing name:				Drawing number:			Sheet:		Issue No.:	
KN-v3-MO2 cable				VKA-2014-03-1			1			
							Num. of sheets:			
							2			
This document is know-how of the CONEL Ltd company Usti n/O. It may not be handed over to third person or abuse without permit.										