



**(c) NOTES:**

1. METALSHELLS: COPPER ALLOY;  
min. 315µin TIN over 40-80µin NICKEL
2. INSULATOR: TPE
3. CLAMPS: STAINLESS STEEL
4. SCREW: STAINLESS STEEL

**(d) 5. CONNECTOR IS PART MARKED: PART NO. CONEC ABC**

No. of pos.	A <sub>-0,76</sub>	B <sub>+0,25</sub>	C	D <sub>-0,3</sub>	(d) E <sub>+25</sub>	(d) F <sub>-0,76</sub>	Part No.: Bulk package	Part No.: (e) Single package
9	31,19	16,79	25,00 <sup>+0,12</sup> <sub>-0,10</sub>	6,12	8,23	12,93	165X14719X	165X14719XE
15	39,52	25,12	33,30 <sup>+0,15</sup>	6,12	8,23	12,93	165X14729X	165X14729XE
25	53,42	38,84	47,04 <sup>+0,13</sup>	5,99	8,23	12,93	165X14739X	165X14739XE
37	69,70	55,30	63,50 <sup>+0,13</sup> <sub>-0,11</sub>	5,99	8,23	12,93	165X14749X	165X14749XE
50	67,31	52,68	61,10 <sup>+0,14</sup> <sub>-0,11</sub>	5,99	10,95	15,75	165X14759X	165X14759XE

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH	tolerance			 dim. in mm	scale: 2:1		material: SEE NOTES  title: HOOD 9 - 50pos. FOR SOCKET CONNECTOR water resiatant, shielded for EMI/RFI		
									material: SEE NOTES
						title: HOOD 9 - 50pos. FOR SOCKET CONNECTOR water resiatant, shielded for EMI/RFI			
						dwg no: Inventor 10		DIN-A4	
						16K1A291A		sh: 1	
						part no: SEE TABLE			

DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name
1 x e	Ä4033	30.06.2011	K.H.
3 x d	Ä3662	23.08.2010	K.H.
1 x c	Ä1912	06.04.2004	Lehmen
3 x b	Ä1788	06.06.2004	Lehmen
a	Origin		

date		name	
drawn	10.09.01	E.Mickenbecker	
appd.	10.09.01	A.Mickenbecker	
norm		DIN 41652	
d-old			

