



**Product:** <u>8732</u> ☑

Electronic, 2 Pr #22 Str TC, PO Ins, 1Pr w/ TC Brd, PVC Jkt, CM

# Request Sample

## **Product Description**

Electronic, 2 Pair 22AWG (7x30) Tinned Copper, PO Insulation, 1 Pair w/ Tinned Copper Braid(62%) Shield, PVC Outer Jacket, CM

### **Technical Specifications**

#### **Product Overview**

Suitable Applications: low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring

# **Physical Characteristics (Overall)**

#### Conductor

AWG	Stranding	Material	No. of Pairs
22	7x30	TC - Tinned Copper	2
Conductor Count: 4		4	
Total I	Total Number of Pairs:		2

#### Insulation

Material	Nominal Wall Thickness
PE - Polyethylene	0.021 in

#### **Color Chart**

Number	Color
1	Black, Clear
2	Black, Clear

## Inner Shield Material

Туре	Layer	Material	Coverage [%]
Braid	1st Pair	TC - Tinned Copper	62 %
Unshielded	2nd Pair		

#### **Outer Shield Material**



## Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.206 x 0.332 in	0.03 in

## **Electrical Characteristics**

## Conductor DCR

Max. Conductor DCR	Nominal Conductor DCR
10.8 Ohm/1000ft	15.4 Ohm/1000ft

### Capacitance

Nom. Capacitance Conductor to Other Conductor to Shield	Nom. Capacitance Conductor to Shield
21 pF/ft	37 pF/ft

#### Impedance

Nominal Characteristic Impedance	Nominal Characteristic Impedance Description
74 Ohm	Shielded pair

#### Current

## Max. Recommended Current [A]

2.3 Amps per conductor @ 25°C

## Voltage

# UL Voltage Rating

300 V RMS (UL AWM Style 2094)

## **Temperature Range**

UL Temp Rating:	60°C (UL AWM Style 2094)
Operating Temp Range:	-20°C To +60°C

## **Mechanical Characteristics**

Bulk Cable Weight:	37 lbs/1000ft
Max Recommended Pulling Tension:	59 lbs
Min Bend Radius/Minor Axis:	2.25 in

#### **Standards**

NEC/(UL) Specification:	СМ
CEC/C(UL) Specification:	СМ
UL AWM Style:	UL Style 2094 (300 V 60°C)
CPR Euroclass:	Eca

## **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS (UL AWM Style 2094)

### Plenum/Non-Plenum

Plenum (Y/N):	No		
i iciidiii (1/14).	140		

## **Part Number**

### Variants

Item #	Color	Putup Type	Length	UPC
8732 0601000	Chrome	Reel	1,000 ft	612825214762
Footnote:			C -	CRATE REEL P

# History

Update and Revision:	Revision Number: 0.307 Revision Date: 04-28-2020

#### © 2020 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.