




THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL INTERNATIONAL RIGHTS RESERVED.

LOC —	DIST —	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
			A	REV PER ECO 09-014236	8-5-09	CT	DW



MOUNTING HOLE PATTERN

1. DESIGNED FOR USE WITH 1/4" THICK STRIPLINE.
2. CAPTURED CENTER CONTACT.

HOUSING BASE PLATES	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	GOLD PLATED PER MIL-G-45204 OVER NICKEL PER AMS-QQ-N-290
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER COPPER PER AMS-2418
MACHINE SCREWS	CORROSION RESISTANT STEEL PER QQ-S-763	GOLD PLATED PER MIL-G-45204 OVER NICKEL PER AMS-QQ-N-290
COMPONENT	MATERIAL	FINISH

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	8-5-09	Tyco Electronics Tyco Electronics Corporation Harrisburg, PA 17105-3608			
		CHK	8-5-09				
DIMENSIONS: INCHES [mm]		APVD	8-5-09	NAME			
		PRODUCT SPEC		SMA STRIPLINE END LAUNCH JACK-TAB TERMINAL			
		APPLICATION SPEC					
MATERIAL		WEIGHT	—	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
SEE TABLE				A2	00779	C=1053479	—
FINISH		CUSTOMER DRAWING		SCALE	5:1	SHEET	1 of 1
SEE TABLE						REV	A