


[illegible]

PIN-OUT CHART

[illegible]

THIS DRAWING IS A CONTROLLED DOCUMENT.		OWN R VESTAL	24JUL2007	 TE Connectivity			
DIMENSIONS:		CHK W. WELLINSKY	24JUL2007				
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPROV W. WELLINSKY	24JUL2007				
mm		NAME	24 WAY ARM PLUG ASSEMBLY WITH SELECT LOAD SHORTING BARS CUSTOMER SPEC.				
		PRODUCT SPEC					
MATERIAL		APPLICATION SPEC	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO	
SEE CHART ABOVE		WEIGHT	A1	00779	C-1924674	-	
CUSTOMER DRAWING		SCALE		3:1	SHEET	4 OF 5	REV

LOC	DIST	REVISIONS					
FX	00	P	LTR	DESCRIPTION	DATE	OWN	APVD
		-		SEE SHEET 1	-	-	-

PIN-OUT CHART																																
		1 / 2																									N	2098376-1	KEY "F"			
		1 / 2																									N	1924686-1	KEY "E"			
		1 / 2																									N	1924685-1	KEY "D"			
		1 / 2																									N	1924684-1	KEY "C"			
		1 / 2																									N	1924683-1	KEY "B"			
		1 / 2																									N	1924682-1	KEY "A"			
5 / 6	3 / 4	1 / 2	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	CPA	ASSEMBLY PART NUMBER	PLUG KEYING OPTION			
SHORTING BAR POSITION			TERMINAL HOLE POSITION																													
CAVITIES W/ A NUMERIC SYMBOL INDICATE SHORTING BAR LOADED			CAVITIES WITH A NUMERIC SYMBOL INDICATE CLOSED TERMINAL HOLE POSITIONS																													
BLANK CAVITIES INDICATE NO SHORTING BAR LOADED			BLANK CAVITIES INDICATE OPEN TERMINAL HOLE POSITIONS																													