

Terminations

SMB - SMC Types

DC - 4.0 GHz - 0.5 Watt Performance

- Low VSWR
- Rugged Stainless Steel Construction
- Small Size, Light Weight
- Bead Chain available on all Models

Midwest Microwave's SMB and SMC Subminiature series of high performance low frequency coaxial Terminations provide temperature stable, ruggedly built, low VSWR performance in a compact lightweight package size. They are useful in commercial low frequency communication systems as well as military applications. Bead Chains are available with the all of the types described.

SPECIFICATIONS

Impedance: 50 Ohms

Frequency: DC - 4.0 GHz

VSWR: 1.15 max @ DC - 2.0 GHz, 1.25 max @ 2.0 - 4.0 GHz

Power: 0.5 Watts max @ 25°C

Operating Temperature Range: -65° to +125°C

Finish: Passivated Stainless Steel

SMB Subminiature

DC - 4.0 GHz	2198 Series	Model Numbers
Jack	Jack with Chain	
TRM-2198-F0-SMB-02		TRM-2198-FC-SMB-02
Plug	Plug with Chain	
TRM-2198-M0-SMB-02		TRM-2198-MC-SMB-02

SMC Subminiature

DC - 4.0 GHz	2199 Series	Model Numbers
Jack	Jack with Chain	
TRM-2199-F0-SMC-02		TRM-2199-FC-SMC-02
Plug	Plug with Chain	
TRM-2199-M0-SMC-02		TRM-2199-MC-SMC-02

Note: Bead Chains are 3.5 inches long.

