




THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION


19

BY AMP INCORPORATED. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
DF	XO		0	RELEASED PER 0H14-0479-04	7-15-04	CT	FB



- FOR USE WITH: RG-405/U .086 [2.18] SEMI-RIGID CABLE.
- SEE INSTRUCTION SHEET 408-6788.
- .500 [12.70] MIN LENGTH OF STRAIGHT CABLE REQUIRED TO APPLY THE CONNECTOR.
- MAT'L: PTFE PER MIL-P-19468.
- MAT'L: BRASS PER MIL-C-50.
- MAT'L: STAINLESS STEEL PER ASTM-A-582.
- MAT'L: BERYLLIUM COPPER PER ASTM-B-196.
- FINISH: GOLD PLATED PER MIL-G-45204.
- FINISH: PASSIVATION PER QQ-P-35.
- FINISH: NICKEL PLATED PER QQ-N-290.
- MAT'L: SILICONE RUBBER PER ZZ-R-765A, CLASS 2B.



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C.C.THOMAS 7-15-04	tyco Electronics TYCO Electronics Harrisburg, PA 17105-3608		1663263-1		
DIMENSIONS: INCHES [mm]		CHK F.BLASICK 7-15-04			PART NO.		
		APVD F.BLASICK 7-15-04			NAME JACK, BULKHEAD, MIL-F SERIES, SMA		
		PRODUCT SPEC 108-12055			RESTRICTED TO		
MATERIAL SEE CALLOUTS		FINISH SEE CALLOUTS	WEIGHT -	SCALE 5:1	CAGE CODE A2 00779	DRAWING NO 1663263	REV 0
CUSTOMER DRAWING					SHEET 1 OF 1		