



P.C.B LAYOUT

N = Number of poles  
 Dim A=Nx5.08  
 Dim B=(N-1)x5.08

	Dim A	Dim B
2-6p	±0.15	±0.10
7-12p	±0.20	±0.20
13-18p	±0.30	±0.25
19-24p	±0.40	±0.30

SIGN	DATE	DESCRIPTION	APPROVER
△	01/18'07	Soldering temperature changed from 245° to 250°	Tason
△	01/18'07	Part NO is Changed	Tason

*THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!*

- Material:
- Item 1 Terminal housing :Thermoplastic (UL 94V-0)
  - Item 2 Clamp : Brass ,Ni plated
  - Item 3 Wire guard solder pin :Brass ,Tin plated
  - Item 4 Terminal screw: Steel Zinc plating"- "slot type

- Electrical
- Voltage rating: 300VAC
  - Current rating: 10A
  - Wire range:
  - Solid wire(AWG): 12-24
  - Stranded wire(AWG): 12-24
  - Torque(Lb-In): 3.5
  - Screw: M2.5
  - Wire strip length: 6-7mm
  - Withstanding Voltage: 1.6KV
  - Operating temperature: -40°C to +115°C
  - △ ● Soldering temperature: 250°C±10°C/5 Sec

△ YN xx 21 5 0 xxxx G

06 2x3P      0000:"@Logo (Standard)      Pb < 40,000ppm (RoHS)  
 09 3x3P      000A:"ANYTEK"Logo  
 ... .. Any special item by  
 72 3x24p      customer request,  
                  please contact sales  
                  department.

<b>ANYTEK</b>		<b>CUSTOMER COPY</b>			
		ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD			
TITLE	YN 5.08 Series				
PART NO.	YNxx2150xxxxG	DWG NO.	8YN0101		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance
		熊海燕 2007.01.25	熊海燕 2007.01.25	UNIT: mm SCALE: NONE SHEET: 01/01	X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°
				REV: D	