

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	B	INITIAL	18SEP2017	YC	CW

NOTES:

1. TECHNICAL CHARACTERISTICS:  
 INSULATION MATERIAL: PC  
 RATED VOLTAGE: 400V  
 RATED CURRENT: 16A  
 INSULATION RESISTANCE:  $\geq 400M\Omega$   
 RATED IMPULSE VOLTAGE: 6KV  
 POLLUTION DEGREE: 3  
 CONTACT RESISTANCE:  $\leq 5m\Omega$   
 FLAMMABILITY: UL94V-0  
 MATING CYCLES: 500 CYCLES  
 WIRE RANGE: 0.5~2.5mm<sup>2</sup>  
 CONTACT TYPE: SPRING TYPE.

注释:

1. 技术参数:  
 绝缘材料: PC  
 额定电压: 400V  
 额定电流: 16A  
 绝缘电阻:  $\geq 400M\Omega$   
 脉冲电压: 6KV  
 污染等级: 3  
 接触电阻:  $\leq 5m\Omega$   
 阻燃等级: UL94V-0  
 插拔次数: 500次  
 接线范围: 0.5~2.5mm<sup>2</sup>  
 接线类型: 弹片连接

T2110052201-007	HMN-005-FS	HMN-005 FEMALE INSERT HMN-005 母插
PART NUMBER 料号	PART DESCRIPTION 描述	
NAME HMN-005-FS		
SIZE	CAGE CODE	DRAWING NO
A3	00779	T2110052201007
CUSTOMER DRAWING		RESTRICTED TO
SCALE 3:2		SHEET 1 OF 1
		REV B

THIS DRAWING IS A CONTROLLED DOCUMENT.	
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:
	0 PLC $\pm$
	1 PLC $\pm$
	2 PLC $\pm$
	3 PLC $\pm$
	4 PLC $\pm$
	ANGLES $\pm$
MATERIAL	FINISH
-	-
-	-

DWN	18SEP2017
YORK CHEN	
CHK	18SEP2017
GINO YAO	
APVD	18SEP2017
CHRIS WANG	
PRODUCT SPEC	108-137119
APPLICATION SPEC	114-137119
WEIGHT	-

1470-19 (3/13)