


N = Number of poles
Dim L = $N \times 5.0$
Dim P = $(N - 1) \times 5.0$

Poles \ Dim.	Dim L	Dim P
2-6p	± 0.15	± 0.10
7-12p	± 0.20	± 0.20
13-18p	± 0.30	± 0.25
19-24p	± 0.40	± 0.30

SIGN	DATE	DESCRIPTION	APPROVER
△	02.08'06	Standard spec is changed.	Marivn
△	12.01'09	Wire range changed from 1.0-2.5mm ² to 0.5-2.5mm ²	Kind
△	12.01'09	Operating Tem. changed from -30°~105 ° to -40°~115°	Kind
△	05/18`10	Solid wire changed from 14-22 to 14-26	Tason
△	05/18`10	Stranded wire changed from 14-22 to 14-26	Tason
△	05/18`10	Torque changed from 2.6Lb-In/0.6Nm to 2.6Lb-In/0.5Nm	Tason
△	11/22`10	The dimensional is changed from 0.95mm to 1.00mm	Tason
△	11/28`13	Update the drawing	Guoxue

Material

- **a** Terminal body : Brass(CuZn) , Tin plated
- **b** Terminal screw: Steel Zinc plating "-" slot type
- **c** Wire guard: Stainless steel
- **d** Terminal housing: Thermoplastic (UL94V-0)

- ⚠ ⚠ Electrical UL/CSA/VDE
 - Voltage rating: 250VAC/250VAC/250VAC
 - Current rating: 16A/16A/16A
 - ⚠ ● Wire range: 0.5-2.5mm²
 - ⚠ ● Solid wire(AWG): 14-26/14-22
 - ⚠ ● Stranded wire(AWG): 14-26/14-22
 - ⚠ ● Torque: 2.6Lb-In/3.5kgf.cm/0.5Nm
 - Screw: M3
 - Wire strip length: 6-7mm
 - Withstanding Voltage: 15KV/15KV/2KV
 - ⚠ ● Operating temperature: -40°C to +115°C
 - ⚠ ● Soldering temperature: 260°C±5°C/5 Sec
 - ⚠ ● SAFETY APPROVAL DETAIL:   
 - Critical dimension: 

△ TA xx 00 x x xxxx G




Color		Dim A		RoHS compliant (lead<4%) In copper Alloy
02	2 POLES	0	4.4mm	0000 Standard @ Logo
03	3 POLES	1	3.8mm	000A Standard ANY Logo
...	...	2	3.5mm	Any special item by customer request, please contact sales department.
24	24 POLES			

ANYTEK

CUSTOMER COPY


ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR, PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		TA - 5.0mm series "+/-"					
PART NO.		TAxx00xxxxxxG		DWG NO.		8TA0001	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance	
			Guoxue 2013.12.03	Guoxue 2013.12.03		UNIT: mm	X. ±0.50
						SCALE: NONE	X.X ±0.30
					SHEET: 01/01	REV.: G	X.XX ±0.10
							X° ±1°



RECOMMENDED PCB LAYOUT

TOP VIEW



N = Number of poles
Dim L=Nx5.0
Dim P=(N-1)x5.0

	Dim L	Dim P
2-6p	±0.15	±0.10
7-12p	±0.20	±0.20
13-18p	±0.30	±0.25
19-24p	±0.40	±0.30

SIGN	DATE	DESCRIPTION	APPROVER
△	12.01'09	Wire range changed from 1.0-2.5mm ² to 0.5-2.5mm ²	Kind
△	12.01'09	Operating Tem. changed from -30°~105 ° to -40°~115°	Kind
△	05/18'10	Solid wire changed from 14-22 to 14-26	Tason
△	05/18'10	Stranded wire changed from 14-22 to 14-26	Tason
△	05/18'10	Torque changed from 2.6Lb-In/0.6Nm to 2.6Lb-In/0.5Nm	Tason
△	02/21'13	update the drawing	Guoxue
△	02/21'13	update the drawing	Guoxue
△	11/28'13	update the drawing	Guoxue

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- ①Terminal body : Brass(CuZn) , Tin plated
- ②Terminal screw: Steel Zinc plating "-" slot type
- ③Wire guard: Stainless steel
- ④Terminal housing: Thermoplastic (UL94V-0)

Electrical UL/CSA/VDE

- Voltage rating: 250VAC/250VAC/250VAC
- Current rating: 16A/16A/16A
- Wire range: 0.5-2.5mm²
- Solid wire(AWG): 14-26/14-22
- Stranded wire(AWG): 14-26/14-22
- Torque: 2.6Lb-In/3.5kgf.cm/0.5Nm
- Screw: M3

- Wire strip length: 6-7mm
- Withstanding Voltage: 1.5KV/1.5KV/2KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C/5 Sec

- SAFETY APPROVAL DATA:    G RoHS compliant (lead<4%) In copper Alloy
- Critical dimension: 

△△ TA xx 01 x x xxxx G

02 2 POLES
03 3 POLES
...
24 24 POLES

Color
0 Black (RAL9005)
2 Red (RAL3001/D)
3 Orange(RAL2011/P)
4 Yellow(RAL1018/A)
5 Green(RAL6018/T)
6 Blue (RAL5015/A)
8 Grey(RAL7035/D)
C Green(RAL6018/U)

Dim A
0 4.4mm
1 3.8mm
2 3.5mm
0000 Standard @ Logo
000A Standard ANY Logo
Any special item by customer request, please contact sales department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		TA - 5.0mm series "-"			
PART NO.	TAXx01xxxxxxG			DWG NO.	8TA0011
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Guoxue 2013.12.03	Guoxue 2013.12.03		Tolerance X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°
SHEET: 01/01		UNIT: mm SCALE: NONE		REV.: F	