







NOTES:


1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. CONTACT RATING: 50mA @12V DC
4. CONTACT MATERIAL: SILVER
5. OPERATING FORCE: 160±50gf
6. TRAVEL: 0.25 +0.2/-0.1
7. CONTACT RESISTANCE: 100mILLI Ohms max.
8. ELECTRICAL LIFE: 100,000 CYCLES
9. PACKAGING:
CARRIER IS FOLDED EVERY 25,
(24) SWITCHES PER FOLD)
(1,000) SWITCHES PER BOX
10. 2002/95/EC (ROHS) COMPLIANT
11. ▲ DENOTES MAJOR DIMENSION.



RECOMMEND P.C.B. HOLES



CONTACT CONFIGURATION



B	UPDATE NOTE, .30 DIM TO .25	1/18/07	TN	E-SWITCH® TL594F160Q			
A	RELEASED FOR PRODUCTION						
REV.	DESCRIPTION	DATE	CHKD				
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED							
TOLERANCES							
0.0		±0.4					
0.00		±0.25					
TITLE							
SCALE	DATE	DR	DWG	REV			
2:1	1/18/2007	TN	P010562	B			