

## Panel feed-through - QPD W 5X1,5 M25 0,35 BK B-S - 1419427

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Panel feed-through, QUICKON connection, number of positions: 5, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, black, Without QUICKON nut, assembly thread: M25, Single wires (welded-on), 1.5 mm², wires cut flat at the end, cable length: 0.35 m, pin assignment: 1 = RD, 2 = BK, 3 = WH, 4 = BN, 5 = VT

RoHS

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 pc                                                                                                    |
| GTIN         | <br>4 055626 173047 |
| GTIN         | 4055626173047                                                                                           |

### Technical data

#### General

|                                       |                    |
|---------------------------------------|--------------------|
| Type                                  | QPD 5x1,5          |
| Length of cable                       | 0.35 m             |
| Color                                 | black              |
| Locking type                          | Screw locking      |
| Connection method                     | QUICKON connection |
|                                       | IDC connection     |
| Number of positions                   | 5                  |
| Note number of positions              | 5                  |
| Tightening torque, union nut          | 8 Nm               |
| Tightening torque, counter nut        | 5 Nm               |
| Number of connections                 | 10                 |
| Conductor cross section flexible min. | 0.5 mm²            |
| Conductor cross section flexible max. | 1.5 mm²            |
| Conductor cross section solid min.    | 0.5 mm²            |
| Conductor cross section solid max.    | 1.5 mm²            |
| Conductor cross section AWG min.      | 20                 |
| Conductor cross section AWG max.      | 16                 |

# Panel feed-through - QPD W 5X1,5 M25 0,35 BK B-S - 1419427

## Technical data

### Cabel

|                                                                             |                                    |
|-----------------------------------------------------------------------------|------------------------------------|
| Structure of individual litz in acc. with VDE 0295 / smallest wire diameter | VDE 0295 class 1 to 6/min. 0.15 mm |
| Wire insulation material                                                    | PVC/PE/TPE/rubber                  |
| Wire diameter including insulation                                          | 1.6 mm ... 3 mm                    |
| Conductor cross section                                                     | 1.5 mm <sup>2</sup>                |
| Position marking                                                            | 1, 2, 3, 4, 5                      |

### Ambient conditions

|                                         |                   |
|-----------------------------------------|-------------------|
| Degree of protection                    | IP66              |
|                                         | IP68 (2 m / 24 h) |
|                                         | IP69K             |
| Ambient temperature (operation)         | -40 °C ... 100 °C |
| Ambient temperature (storage/transport) | -40 °C ... 100 °C |
| Temperature when conductor connected    | -5 °C ... 50 °C   |

### Electrical characteristics

|                                |        |
|--------------------------------|--------|
| Nominal current I <sub>N</sub> | 17.5 A |
| Rated current                  | 17.5 A |
| Rated voltage (III/3)          | 690 V  |
| Rated voltage (III/2)          | 1000 V |
| Rated voltage (II/2)           | 1000 V |
| Rated surge voltage (III/3)    | 6 kV   |
| Rated surge voltage (III/2)    | 8 kV   |
| Rated surge voltage (II/2)     | 8 kV   |

### Mechanical characteristics

|                          |         |
|--------------------------|---------|
| QUICKON connectability   | max. 10 |
| Category of shock impact | IK07    |

### Material data

|                                        |               |
|----------------------------------------|---------------|
| Contact material                       | Cu            |
| Contact surface material               | silver-plated |
| Contact carrier material               | PA            |
| Insulating material                    | PA            |
| Flammability rating according to UL 94 | V0            |
| Overvoltage category                   | III           |
| Degree of pollution                    | 3             |


### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V0 |
|----------------------------------------|----|


## Drawings

## Panel feed-through - QPD W 5X1,5 M25 0,35 BK B-S - 1419427

Dimensional drawing



Dimensional drawing



Panel cutout

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>