





N=Number of contacts

Cutout dimensions



SECTION A-A

DIMENSION $\triangle_3$

Dim A	$N \times 3.81 + 14.39$
Dim B	$(N-1) \times 3.81$
Dim C	$(N-1) \times 3.81 + 10.0$
Dim D	$(N-1) \times 3.81 + 13.95$

Poles	Tolerance
2pole~5pole	± 0.20
6pole~10pole	± 0.30
11pole~15pole	± 0.35
16pole~24pole	± 0.40

SIGN	DATE	DESCRIPTION	APPROVER
△	3/24'06	Add Cutout dimensions	Marvin
△	12/14'06	Removed soldering temperature standard.	Marvin
△	2009.7.3	Add the tolerance table	Jacke
△	2009.7.3	The temperature changed from -30°C +105°C to -40°C +115°C	Jacke
△	2013.10.17	Update the drawing	Chen Bo
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

Material:

- Item (a) Solder Pin: Brass , Tin plated.
- Item (b) Flange screw nut: brass M2.5.
- Item (c) Terminal (housing): Thermoplastic(UL94 V-0)

- 2** Electrical cULus
- Voltage rating: 300VAC
 - Current rating: 10 A.
 - Withstanding Voltage: 1.6kv
- 4**
- Operating temperature: -40°C to +115°C
 - Safety Approval:  cULus
 - Critical dimension: 

VZ xx 30 x 0 xxxx G

Solid Block	_____
02	2 CONTACTS
03	3 CONTACTS
...	...
24	24 CONTACTS

COLOR

0	Black (RAL9005)
2	Red (RAL3001/D)
3	Orange(RAL2011/P)
4	Yellow(RAL1018/A)
5	Green(RAL6018/T)
6	Blue (RAL5015/A)
8	Grey(RAL7035/D)
9	White(RAL1102)
C	Green(RAL6018/U)

— G RoHS compliant
(lead<4%)
In copper Alloy

000 0 Standard @ Logo
000 A Standard ANY Logo
Any special item by
customer request,
please contact sales
department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	VZ-3.81 Series						
PART NO.	VZxx30x0xxxxG			DWG NO.	8VZ0001		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			Tolerance
		Chen Bo 10/17`13	Chen Bo 10/17`13		UNIT: mm	X.	±0.50
				SHEET: 01/01	SCALE: NONE	X.X	±0.30
					REV: G	X.XX	±0.10
						X°	±1°