










Max. Temperature: 260° during 10 seconds.

0955 269 3821 741	1	M3	Black insulator	Reel Packaging: 140 connectors (See details on page2/2)		
0955 269 3822 741	1	4-40 UNC				
0955 269 6821 741	2	M3				
0955 269 6822 741	2	4-40 UNC				
0955 269 7821 741	3	M3				
0955 269 7822 741	3	4-40 UNC				
Part number	PL	Screw lock	Index designation			
 All Dimensions in mm Original Size DIN A 3		Techn. Character.		Free size tolerances		
				D-Sub SMT, 15 poles Male, Straight with screw locks and ground pins		
EC04070	17-Nov-11	Johnson.S	Zhuhai HARTING Limited 		TB 09 55 269 x82x	Page 1 / 2
Mod.	Dat.	Name			Sub.	



Detail A



See TB 09 55 269 x82x folio 1/2
for connector dimensions
and PCB layout

Packaging in accordance with
EIA 481-2.

0955 269 3821 741	1	M3	Black insulator	Reel Packaging: 140 connectors
0955 269 3822 741	1	4-40 UNC		
0955 269 6821 741	2	M3		
0955 269 6822 741	2	4-40 UNC		
0955 269 7821 741	3	M3		
0955 269 7822 741	3	4-40 UNC	Index designation	
Part number	PL	Screw lock		

All Dimensions in mm Original Size DIN A 3			Techn. Character.			Free size tolerances	
				Dat.	Name	Scale	D-Sub SMT, 15 poles Male, Straight with screw locks and ground pins
			Detail.	25-Oct-11	Johnson.S		
			Insp.	17-Nov-11	Steven.W		
			Stand.	17-Nov-11	Steven.W		TB 09 55 269 x82x
EC04070	17-Nov-11	Johnson.S	Zhuhai HARTING Limited				
Mod.	Dat.	Name				Sub.	Page 2/2