

Share:



## APC Performance SurgeArrest 8 outlets with Phone & Coax Protection 230V Germany

PMF83VT-GR



Description: Maximum Power Surge Protection for Computers, Notebooks and Other Electronics

Includes : User Manual


[Product Overview](#)
[Technical Specifications](#)
[Documentation](#)

### Output

[Print Technical Specification](#)

Number of Outlets	8.0
Receptacle Style	CEE 7 Schuko

### Input

Nominal Input Voltage	230V
Input frequency	50 Hz
Input Connections	Schuko CEE 7/7P
Cord Length	3meters

Number of Power Cords	1
Input Power	2300.0Watts
Maximum Input Current	10.0A

## Surge Protection and Filtering

---

Surge energy rating	2690Joules
Data Line Protection	RJ-11 Modem/Fax protection, Coaxial cable for CATV/SATV/modem/Audio-Video (coax connector)
ts_nm_surge_response	1ns
Peak Current Common Mode	48kAmps
Peak Current Normal Mode	60 (/PH)kAmps

## Physical

---

Maximum Height	62mm , 6.2cm
Maximum Width	327mm , 32.7cm
Maximum Depth	110mm , 11.0cm
Net Weight	0.94kg
Shipping weight	1.08kg
Shipping Height	64mm , 6.4cm
Shipping Width	365mm , 36.5cm
Shipping Depth	170mm , 17.0cm
Color	White
Master Carton Dimensions (Length x Width x Height)	365 x 213 x 387mm
Master Carton Units	6.0
Master Carton Weight	6.93
Units per Pallet	78.0

## Environmental

---

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95% no %
Operating Elevation	0-15000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters

## Conformance

Approvals	CE
Equipment protection policy	Lifetime : 100000 Euro
Standard warranty	Lifetime (European Union countries only)

## Sustainable Offer Status

RoHS	Compliant
------	-----------

Sign up to stay up to date with best practices, new solutions and special offers.



Email

OK

WHO WE ARE

CONNECT WITH US

FIND A RESELLER

Zip/Postal Code

FIND

## CATALOG KEYCODE

Enter Key Code

GO



[TERMS & CONDITIONS](#) >

[PRIVACY STATEMENT](#) >

© 2016, APC by Schneider Electric