



V1 FILAMENT:
 5.2-5.5 VDC
 FILAMENT CURRENT:
 45 +/- 10 mA DC
V2 ELECTRODE SOURCE:
 24-26 V DC TYP.
 ELECTRODE CURRENT:
 14 +/- 3.0 mA DC
BALLAST RESISTOR:
 1K TYP.
ELECTRODE RUNNING VOLTAGE:
 10 +/- 3.0 V DC
TOTAL LAMP WATTAGE:
 .40 TYP.
INTENSITY
 3000 Cd/m2 MIN.
LIFE HOURS:
 *15,000

*TO 50% OUTPUT INTENSITY

JKL PART NO.: BGF717-22

			METRIC THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		JKL COMPONENTS CORPORATION			
					TITLE MINIATURE HOT CATHODE FLUORESCENT LAMP (ACORN)					
B RELEASED TO CAD 5/9/01			DRAWN BY L. WENGSTROM		APPVD BY DATE F.D. 5/9/01		SIZE A	FSCM NO. 55335	DRAWING NO. BGF717-22	
A LIFE HRS-LEAD LENGTH 11/9/99 RELEASED 7/2/99			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 7/2/99	REVISION DATE 5/9/01	REV. NO. B	SHEET 1 OF 1
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE								