XGSZ12E1201



Main

Range of product	OsiSense XG
Accessory / separate part category	Connection accessories
Accessory / separate part type	Connecting cable
Product or component type	Ethernet copper cable
Product compatibility	XGSZ33ETH XGSZ33EIP
Accessory / separate part destination	Ethernet network

Complementary

Cable length	3.28 ft (1 m)	
Transmission rate	100 Mbit/s	
Transmission support medium	2 twisted shielded pairs	
Communication network category	5e	
AWG gauge	AWG 26	
Electrical connection	1 male connector, M12 straight connector with 4 pin(s) - encoding type: D coding 1 male connector, M12 straight connector with 4 pin(s)	
Conductor material	Copper	
Cover material	PUR	
Product weight	0.17 lb(US) (0.075 kg)	

Environment

IP degree of protection	IP67	
standards	EIA/TIA-568 IEC 60754-1 ISO/IEC 11801 Ed.2, 2002	
environmental characteristic	RoHS compliant	

Offer Sustainability

onor ouclamability	
Not Green Premium product	Not Green Premium product
Compliant - since 1210 - Schneider Electric declaration of conformity	Compliant - since 1210 - Schneider Electric declaration of conformity
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Stat of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www n65warnings ca gov	For more information go to www p65warnings ca gov

Wiring Diagram

M12		Ī		M12
1	TD+	1	TD+	1
3	TD-	$H \rightarrow H$	TD -	3
2	RD+	$H \nearrow H$	RD+	2
4	RD -		RD -	4