

## Between Series Adaptor 31\_PC24-SK-50-1/199\_N

### Description

Adaptor jack/jack  
PC 2.4 jack (female) / SK jack (female)

For Test & Measurement applications  
Precision adaptor

Interface standards  
Series PC 2.4 - IEC 60169-38  
Series SK - MIL-STD-348A/323



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	40 GHz
Frequency range	DC to 40 GHz
Return loss	≥ 25 dB
Electrical length	16.1 mm

#### Mechanical Data

Number of matings	500
Weight	0.0041 kg

#### Environmental Data

Operating temperature	-40 °C to 125 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Interface - PC 2.4 jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PPE (Polyphenylene ether, PPO)	

Interface - SK jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PPE (Polyphenylene ether, PPO)	

### Related Documents

Outline drawing	DOU-00062612
-----------------	--------------

### Ordering Information

Single package	31_PC24-SK-50-1/199_NE
----------------	------------------------

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[31\\_PC24-SK-50-1/199\\_NE](#)