

Audio, Daten & Signal, Inline Socket, 6.3 mm, 3-pole, solder terminal, shielded



Description

- Solder terminal:
- Audio entrances and exits
- Data and Signal transfer
- Data and Signal Connectors 3-pole, shielded, straight

References

Alternative: Housing insulated

Weblinks


[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)

Technical Data


Diameter	6.3 mm
Number of Poles	3-pole
Ratings DC	2 A / 12 VDC
Ratings AC	2 A / 12 VAC
Dielectric Strength	1000 VDC
Insulation Resistance	> 10000 MΩ @ 500 VDC

Allowable Operation Temp.	-20 °C to 70 °C
Terminal	solder terminal
Housing	screened
Style	straight
Lifetime	10000 Insertions

Dimensions



Diagrams



Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Data and Signal Plug/ Sockets	6.3	3-pole	solder terminal	4803.3300

Packaging unit 100 Pcs

Mating Inlets/Plugs

Category / Description

[Data and Signal Plug/Socket Overview complete](#)



Audio, Data & Signal, Plug, 6.3 mm, 3-pole, solder terminal, shielded	4803.1300
Audio, Data & Signal, Plug, 6.3 mm, 3-pole, solder terminal, insulated	4803.1310
Audio, Data & Signal, Plug, 6.3 mm, 3-pole, solder terminal, insulated, angled	4803.1320
Data and Signal Plug/Socket further types to 4803 UK-Stecker, D=6,5mm	