


NOTE:

- 1. Material: HOUSING: HIGH TEMPERATURE THERMOPLASTIC, UL 94 V-0 FLAME RETARDANT. TERMINAL: HIGH CONDUCTIVITY COPPER ALLOY. PLATING SPEC AS BELOW: Ni 50u" UNDER PLATED. Au 30u" OVER CONTACT AREA.(ONE SIDE) Matte Tin 120u" OVER SOLDERING AREA.)
- 2. PACKING SPEC. GS-14-937.
- 3. PRODUCT SPEC. GS-12-338.
- 4. PART NUMBER SCHEME:(EX. 10046971-038 LF)

5. PART NUMBER 10046971-038LF MEETS EUROPEAN UNION DIRECTIVE AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A CIRCUIT BOARD.

REV	ECN NUMBER	REV'D BY	DATE
A	-	HZ	2012-01-02

LEAD FREE



SECTION C-C



BOARD RETENTION PINS SECTION F-F



Copyright FCI.

spec ref	*	dr	Wei-Long Zhang	2011/12/07	projection 	mm ←→	size	A4	scale	1.000		
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED	eng	Wei-Long Zhang	2012/01/03			product family	PEC	ecn no	-	rel level	Released
		chr	Eleven Hu	2012/01/04				surface	✓	linear		0.X ± 0.50 0.XX ± 0.25 0.XXX ± 0.13
appr	Pei-Ming Zheng	2012/01/04	www.fci.com		title	POWER EDGE CONNECTOR OF VERTICAL TYPE (23PX2)		cat. no.	*	Product - Customer Drw		
surface		FCI		www.fci.com	cat. no.	*	Product - Customer Drw	sheet 1 of 2	rev	A		
linear		0.X ± 0.50		www.fci.com		cat. no.	*	Product - Customer Drw	sheet 1 of 2	rev		
angular		0° ± 2°		www.fci.com		cat. no.	*	Product - Customer Drw	sheet 1 of 2	rev		



RECOMMENDED PC BOARD LAYOUT
AND THE THICKNESS IS 3.18mm



Copyright FCI.

spec ref	*	dr	Wei-Long Zhang	2011/12/07	projection 	mm ←→	size	A4	scale	1.000		
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED	eng	Wei-Long Zhang	2012/01/03			ecn no	-				
		chr	Eleven Hu	2012/01/04								
surface	✓	appr	Pei-Ming Zheng	2012/01/04	product family	PEC	rel level	Released				
	linear	0.X	± 0.50		title	POWER EDGE CONNECTOR OF		dwg no	10046971-038		rev	A
		0.XX	± 0.25			cat. no.	Product - Customer Drw		sheet 2 of 2			
		0.XXX	± 0.13									
	angular	0°	± 2°	www.fci.com								

PrdE File - REV C - 2009-06-09