

| 9808  | 9101  | 5650  | 8679  |
|---|---|---|---|
|   |   |   |   |
| <b>9808-0-15-XX-16-XX-04-0</b><br>Press-fit in 1,70 mounting hole | <b>9101-0-15-XX-16-XX-10-0</b><br>Press-fit in 1,70 mounting hole | <b>5650-0-19-XX-16-XX-10-0</b><br>Press-fit in 1,70 mounting hole | <b>8679-0-15-XX-16-XX-10-0</b><br>Solder mount in 1,80 min. mounting hole |

| 8827  | 6021  | 1873  |
|---|---|---|
|   |   |   |
| <b>8827-0-15-XX-16-XX-04-0</b><br>Press-fit in 1,55 mounting hole | <b>6021-0-15-XX-16-XX-10-0</b><br>Solder mount in 1,57 min. mounting hole | <b>1873-0-15-XX-16-XX-04-0</b><br>Press-fit in 1,68 mounting hole |

|  |  |  |  |
|--|--|--|--|
|  |  |  |  |
|--|--|--|--|

|  |   |
|--|---|
| <p><b>SPECIFICATIONS</b></p> <p><b>SHELL MATERIAL:</b><br/>Brass Alloy 360, 1/2 Hard</p> <p><b>CONTACT MATERIAL:</b><br/>Beryllium Copper Alloy 172, HT</p> <p><b>DIMENSION IN INCHES</b><br/><b>TOLERANCES ON:</b><br/>LENGTHS: ±0,13<br/>DIAMETERS: ±0,05<br/>ANGLES: ± 2°</p> | <p><b>ORDER CODE: XXXX - X - 1X - XX - 16 - XX - XX - 0</b></p> <p><b>BASIC PART #</b> →</p> <p><b>SPECIFY SHELL FINISH:</b> →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL<br/>             ◇ 80 5,08µm TIN OVER NICKEL (RoHS)<br/>             ◇ 15 0,25µm GOLD OVER NICKEL (RoHS)</p> <p><b>SPECIFY CONTACT FINISH:</b> →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL<br/>             ◇ 80 5,08µm TIN OVER NICKEL (RoHS)<br/>             ◇ 27 0,76µm GOLD OVER NICKEL (RoHS)</p> <p style="text-align: center;"><b>CONTACT</b><br/>#16 CONTACT (DATA ON PAGE 222)</p> |
|--|---|

