




## HEYClip™ Countersunk Type H Rivets

- Flat, **chamfered rivet head** for **easier disassembly** when required.
- Accommodate countersunk hole specification DIN ISO 7721.
- The "H" type rivet is designed with a flat head for fast and easy installation, without any tools.
- Simply place rivet into the hole and press down on the head to fasten.
- Part Description Key: PRH X-Y where X = Mounting Hole Diameter (inches) and Y = minimum Panel Thickness (inches).
- Standard Material: Nylon 6. Nylon 6/6 UL 94V-0 available by special order, consult Heyco.
- Standard Pack - 1,000/bag.

| WILL FIT THESE PANELS |     |                           |      |     |     | PART NO. |       |             | DESCRIPTION | PART DIMENSIONS |      |               |     |                 |     | EXTRACTION FORCE |       |
|-----------------------|-----|---------------------------|------|-----|-----|----------|-------|-------------|-------------|-----------------|------|---------------|-----|-----------------|-----|------------------|-------|
| MOUNTING HOLE DIA.    |     | ASSEMBLED PANEL THICKNESS |      |     |     | Black    | White | V-0 Black * |             | A Length        |      | B Head Height |     | C Head Diameter |     | N                | Style |
|                       |     | Min.                      | Max. |     |     |          |       |             |             |                 |      |               |     |                 |     |                  |       |
| in.                   | mm. | in.                       | mm.  | in. | mm. |          |       |             |             | in.             | mm.  | in.           | mm. | in.             | mm. |                  |       |
| PRH Series            |     |                           |      |     |     |          |       |             |             |                 |      |               |     |                 |     |                  |       |
| .102                  | 2,6 | .22                       | 5,5  | .26 | 6,5 | 9118     | 9119  | 9118F       | PRH 102-217 | .33             | 8,5  | .03           | 0,7 | .18             | 4,6 | 49               | 1     |
|                       | 3,1 | .04                       | 1,0  | .08 | 2,0 | 9156     | 9157  | 9156F       | PRH 122-039 | .14             | 3,5  |               |     |                 |     | 78               | 1     |
|                       |     | .08                       | 2,0  | .12 | 3,0 | 9158     | 9159  | 9158F       | PRH 122-079 | .18             | 4,5  | .04           | 1,0 | .25             | 6,4 |                  |       |
|                       |     | .12                       | 3,0  | .16 | 4,0 | 9160     | 9161  | 9160F       | PRH 122-118 | .22             | 5,5  |               |     |                 |     |                  |       |
|                       |     | .16                       | 4,0  | .19 | 5,0 | 9162     | 9163  | 9162F       | PRH 122-157 | .26             | 6,5  |               |     |                 |     |                  |       |
|                       |     | .20                       | 5,0  | .24 | 6,0 | 9164     | 9165  | 9164F       | PRH 122-197 | .31             | 7,5  | .04           | 1,0 | .24             | 6,0 |                  |       |
|                       |     | .22                       | 5,5  | .26 | 6,5 | 9166     | 9167  | 9166F       | PRH 122-217 | .32             | 8,0  |               |     |                 |     |                  |       |
|                       |     | .26                       | 6,5  | .30 | 7,5 | 9168     | 9169  | 9168F       | PRH 122-256 | .35             | 9,0  | .04           | 1,0 | .25             | 6,4 |                  |       |
|                       |     | .30                       | 7,5  | .34 | 8,5 | 9170     | 9171  | 9170F       | PRH 122-295 | .39             | 10,0 |               |     |                 |     |                  |       |
|                       | 3,6 | .04                       | 1,0  | .08 | 2,0 | 9172     | 9173  | 9172F       | PRH 142-039 | .14             | 3,5  | .04           | 1,0 | .25             | 6,4 | 118              | 2     |
|                       |     | .08                       | 2,0  | .12 | 3,0 | 9174     | 9175  | 9174F       | PRH 142-079 | .19             | 4,5  |               |     |                 |     |                  |       |
|                       |     | .12                       | 3,0  | .16 | 4,0 | 9176     | 9177  | 9176F       | PRH 142-118 | .22             | 5,5  |               |     |                 |     |                  |       |
|                       |     | .14                       | 3,5  | .18 | 4,5 | 9178     | 9179  | 9178F       | PRH 142-138 | .24             | 6,0  | .04           | 1,0 | .24             | 6,0 |                  |       |
|                       |     | .18                       | 4,5  | .22 | 5,5 | 9180     | 9181  | 9180F       | PRH 142-177 | .28             | 7,0  |               |     |                 |     |                  |       |
|                       |     | .22                       | 5,5  | .26 | 6,5 | 9182     | 9183  | —           | PRH 142-217 | .32             | 8,0  |               |     |                 |     |                  |       |

Standard colors black and white.

\*Black nylon 6/6 UL 94V-0.




STYLE 1



STYLE 2



PRH Series



DR Series



## HEYClip™ Push (aka Drive) Rivets

- Install by placing rivet into hole and pushing the drive pin into the rivet to expand legs and lock in place.
- No tools required.
- Part Description Key: DR X-Y where X = Mounting Hole Diameter (inches) and Y = minimum Panel Thickness (inches).
- Standard Pack - 1,000/bag.

| WILL FIT THESE PANELS |     |                           |      |     |      | PART NO. |         | DESCRIPTION | PART DIMENSIONS |      |               |     |                 |      |
|-----------------------|-----|---------------------------|------|-----|------|----------|---------|-------------|-----------------|------|---------------|-----|-----------------|------|
| MOUNTING HOLE DIA.    |     | ASSEMBLED PANEL THICKNESS |      |     |      | Black    | Natural |             | A Length        |      | B Head Height |     | C Head Diameter |      |
|                       |     | Min.                      | Max. |     |      |          |         |             |                 |      |               |     |                 |      |
| in.                   | mm. | in.                       | mm.  | in. | mm.  |          |         |             | in.             | mm.  | in.           | mm. | in.             | mm.  |
| DR Series             |     |                           |      |     |      |          |         |             |                 |      |               |     |                 |      |
| .161                  | 4,1 | .10                       | 2,5  | .14 | 3,5  | 9141     | 9142*   | DR 161-098  | .20             | 5,0  | .09           | 2,2 | .31             | 8,0  |
| .187                  | 4,8 | .04                       | 1,0  | .38 | 9,5  | 9184     | 9185    | DR 189-039  | .42             | 10,7 | .06           | 1,5 | .28             | 7,1  |
|                       |     | .16                       | 4,0  | .28 | 7,1  | 9186     | 9187    | DR 189-158  | .38             | 9,7  | .06           | 1,5 | .43             | 10,9 |
| .218                  | 5,5 | .09                       | 2,4  | .16 | 4,0  | 9188     | 9189    | DR 217-094  | .45             | 11,4 | .08           | 2,0 | .37             | 9,4  |
| .250                  | 6,4 | .06                       | 1,5  | .25 | 6,4  | 9190     | 9191    | DR 252-059  | .36             | 9,2  | .19           | 4,7 | .44             | 11,1 |
|                       |     | .28                       | 7,1  | .50 | 12,7 | 9192     | 9193    | DR 252-280  | .62             | 15,8 | .08           | 2,0 | .47             | 11,9 |

Standard colors black and natural.

\*Standard color white.

Quick  
Specs

|                     |                              |                |
|---------------------|------------------------------|----------------|
| Material            | PRH - Nylon 6                | DR - Nylon 6/6 |
| Flammability Rating | 94V-2                        |                |
| Temperature Range   | -4°F (-18°C) to 185°F (85°C) |                |