



(4) PRONGS TO BE BENT DOWN AS SHOWN

MUST BE LANCED FREE (4 PLACES) (SEE NOTE 2)

- NOTES:
1. I.D. TO BE .455 "GO"/.471 "NO GO" WHEN MEASURED IN DIRECTION SHOWN.
 2. TO INSURE LANCE IS CUT FREE, PART TO BE BENT 90° AT EACH LANCE.

VENDOR: ASQUARED
P/N: PO-659460-1

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M
----	--------------	-------------	-------	-----

BILL OF MATERIAL

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

O	DENOTES CRITICAL CHARACTERISTICS.
CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE
ST	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.
CP	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.

QTY	REP	REV	DATE	BY	APPD	CHK	LTR	REV
							G	39107C - REVISED & REDRAWN ON NEW FORMAT 4/21/98 JMB

COPIES TO	MATL SPEC AISI C-1050 ANNEALED .625 W. x .012 THK HEAT TREAT TO RC 46-50	FINISH BLACK OXIDE
1 9 18	DRW JMB	DATE 3/2/98 SCALE 2=1
2 10 19	CHK	DATE SUPER DRW
3 12 20	APPD	DATE RAW STK WT
4 13 21	TOLERANCE UNLESS OTHERWISE SPECIFIED TWO PLACE DEC ±.01 FRACTIONAL THREE PLACE DEC ±.005 ANGULAR	
5 14 23		
6 15 33		
7 16 43		
8 17 53		

TITLE PUSH-ON ROUND

REVISION **DRWG. NO.**
 DES PLAINES, ILLINOIS 60016
 -903-114

CAD GENERATED DRAWING - NO PENCIL CHANGES ALLOWED